

In the claims:

Following is a complete set of claims as amended with this Response.

1. (Currently Amended) A method comprising:

transmitting a first broadcast message in a broadcast channel at a first specific time within a first assigned slot of a predetermined frame from a first ~~base station~~ broadcasting terminal of a radio communications system, the first broadcast message including a first broadcast information sequence;

transmitting a second broadcast message in the broadcast channel at a second specific time within a second assigned slot of the predetermined frame from a second ~~base station~~ broadcasting terminal of the radio communications system, the second broadcast message including a second broadcast information sequence; and

receiving a message from a user terminal ~~at the first base station~~, the received message being timed relative to the first broadcast message to distinguish the received message as being directed to the first broadcasting terminal. having a timing relationship with the predetermined frame; and

~~determining at the first base station whether the received message is directed to the first base station or not directed to the first base station based on the timing relationship.~~

2. (Currently Amended) The method of Claim 1, further comprising

transmitting further broadcast messages in the broadcast channel at further specific times within further assigned slots of a predetermined frame from further ~~base stations~~ broadcasting terminals of the radio communications system, the further broadcast messages including further broadcast information sequences.

Attorney Docket No. 015685P052
Application No. 09/675,274

3. (Original) The method of Claim 1, wherein the predetermined frame is a repeating frame.
4. (Currently Amended) The method of Claim 1, wherein the specific transmission times are determined based on a common timing reference received by each ~~b-base station~~ broadcasting terminal.
5. (Currently Amended) The method of Claim 4, wherein the common timing reference is a satellite clock transmission received by a satellite receiver at each ~~base station~~ broadcasting terminal.
6. (Currently Amended) The method of Claim 1, wherein the respective broadcast information sequences includes a code to identify the respective ~~base station~~ broadcasting terminal.
7. (Currently Amended) The method of Claim 6, wherein the code to identify the ~~base station~~ broadcasting terminal comprises a base station color code.
8. (Previously Presented) The method of Claim 1, wherein the respective broadcast information sequences include a power sequence that is related to the power used to transmit the respective broadcast message.
9. (Currently Amended) The method of Claim 1, wherein the respective broadcast information sequences include a load sequence that is related to the current traffic load at the respective ~~base station~~ broadcasting terminal.

10. (Currently Amended) A method comprising:

receiving a first broadcast message in a broadcast channel at a first specific time within a first assigned slot of a predetermined frame from a first ~~base station~~ broadcasting terminal of a radio communications system, the first broadcast message including a first broadcast information sequence;

receiving a second broadcast message in the broadcast channel at a second specific time within a second assigned slot of the predetermined frame from a second ~~base station~~ broadcasting terminal of the radio communications system, the second broadcast message including a second broadcast information sequence; and

transmitting a message from a user terminal having a timing relationship with the predetermined frame, the message being directed to a specific broadcasting terminal based on the timing relationship with the predetermined frame indicating whether the message is directed to the first base station or to the second base station.

11. (Currently Amended) The method of Claim 10, further comprising

receiving further broadcast messages in the broadcast channel at further specific times within further assigned slots of a predetermined frame from further ~~base stations~~ broadcasting terminals of the radio communications system, the further broadcast messages including further broadcast information sequences.

12. (Original) The method of Claim 10, wherein the predetermined frame is a

repeating frame.

13. (Currently Amended) The method of Claim 10, wherein the specific transmission times are determined based on a common timing reference received by each ~~base-station~~ broadcasting terminal.

14. (Currently Amended) The method of Claim 13, wherein the common timing reference is a satellite clock transmission received by a satellite receiver at each ~~base-station~~ broadcasting terminal.

15. (Currently Amended) The method of Claim 10, wherein the respective broadcast information sequences include a code to identify the respective ~~base-station~~ broadcasting terminal.

16. (Currently Amended) The method of Claim 15, wherein the code to identify the respective ~~base-station~~ broadcasting terminal comprises a base station color code.

17. (Previously Presented) The method of Claim 10, wherein the respective broadcast information sequences include a power sequence that is related to the power used to transmit the respective broadcast message.

18. (Currently Amended) The method of Claim 10, wherein the respective broadcast information sequences include a load sequence that is related to the current traffic load at the respective ~~base-station~~ broadcasting terminal.

19. (Currently Amended) A machine-readable medium having stored thereon data representing sequences of instructions which, when executed by a machine, cause the machine to perform operations comprising:

transmitting a first broadcast message in a broadcast channel at a first specific time within a first assigned slot of a predetermined frame from a first ~~base station~~ broadcasting terminal of a radio communications system, the first broadcast message including a first broadcast information sequence;

transmitting a second broadcast message in the broadcast channel at a second specific time within a second assigned slot of the predetermined frame from a second ~~base station~~ broadcasting terminal of the radio communications system, the second broadcast message including a second broadcast information sequence; and

receiving a message from a user terminal ~~at the first base station~~, the received message being timed relative to the first broadcast message to distinguish the received message as being directed to the first broadcasting terminal. having a timing relationship with the predetermined frame; and

~~determining at the first base station whether the received message is directed to the first base station or not directed to the first base station based on the timing relationship.~~

20. (Currently Amended) The medium of Claim 19, the instructions causing the machine to perform further operations comprising transmitting further broadcast messages in the broadcast channel at further specific times within further assigned slots of a predetermined frame from further ~~base stations~~ broadcasting terminals of the radio

communications system, the further broadcast messages including further broadcast information sequences.

21. (Currently Amended) The medium of Claim 19, wherein the specific transmission times are determined based on a common timing reference received by each ~~base-station~~ broadcasting terminal.

22. (Currently Amended) The medium of Claim 19, wherein the respective broadcast information sequences include a code to identify the respective ~~base-station~~ broadcasting terminal.

23. (Previously Presented) The medium of Claim 19, wherein the respective broadcast information sequences include a power sequence that is related to the power used to transmit the respective broadcast message.

24. (Currently Amended) The medium of Claim 19, wherein the respective broadcast information sequences include a load sequence that is related to the current traffic load at the respective ~~base-station~~ broadcasting terminal.

25. (Currently Amended) A machine-readable medium having stored thereon data representing sequences of instructions which, when executed by a machine, cause the machine to perform operations comprising:

receiving a first broadcast message in a broadcast channel at a first specific time within a first assigned slot of a predetermined frame from a first ~~base-station~~ broadcasting terminal of a radio communications system, the first broadcast message including a first broadcast information sequence;

receiving a second broadcast message in the broadcast channel at a second

specific time within a second assigned slot of the predetermined frame from a second base station broadcasting terminal of the radio communications system, the second broadcast message including a second broadcast information sequence; and

transmitting a message from a user terminal having a timing relationship with the predetermined frame, the message being directed to a specific broadcasting terminal based on the timing relationship with the predetermined frame indicating whether the message is directed to the first base station or to the second base station.

26. (Currently Amended) The medium of Claim 25, the instructions causing the machine to perform further operations comprising transmitting further broadcast messages in the broadcast channel at further specific times within further assigned slots of a predetermined frame from further base stations broadcasting terminals of the radio communications system, the further broadcast messages including further broadcast information sequences .

27. (Currently Amended) The medium of Claim 25, wherein the respective broadcast information sequences include a code to identify the respective base station broadcasting terminal.

28. (Previously Presented) The medium of Claim 25, wherein the respective broadcast information sequences include a power sequence that is related to the power used to transmit the respective broadcast message.

29. (Currently Amended) The medium of Claim 25, wherein the respective broadcast information sequences include a load sequence that is related to the current traffic load at the respective base station broadcasting terminal.

Attorney Docket No. 015685P052
Application No. 09/675,274

30. (Currently Amended) An apparatus comprising:

a first transmitter at a first ~~base-station~~ broadcasting terminal of a radio communications system to transmit a first broadcast message in a broadcast channel at a first specific time within a first assigned slot of a predetermined frame, the first broadcast message including a first broadcast information sequence;

a second transmitter at a second ~~base-station~~ broadcasting terminal of the radio communications system to transmit a second broadcast message in the broadcast channel at a second specific time within a second assigned slot of the predetermined frame, the second broadcast message including a second broadcast information sequence; and

a receiver at the first and second ~~base-stations~~ broadcasting terminas, respectively to receive a message from a user terminal, the received message being timed relative to the first broadcast message to distinguish the received message as being directed to the first broadcasting terminal ~~having a timing relationship with the predetermined frame, the timing relationship indicating whether the received message is directed to the first base station or directed to the second base station.~~

31. (Currently Amended) The apparatus of Claim 30, further comprising further transmitters of further ~~base-station~~ broadcasting terminal s of the radio communications system to transmit further broadcast messages in the broadcast channel at further specific times within further assigned slots of the predetermined frame, the further broadcast messages including further broadcast information sequences.

32. (Currently Amended) The apparatus of Claim 30, wherein the first and the second ~~base stations~~ broadcasting terminals further comprise a timing reference receiver to receive a timing reference common to the first ~~base station~~ broadcasting terminal and the second ~~base station~~ broadcasting terminal.

33. (Currently Amended) The apparatus of Claim 30, wherein the respective broadcast information sequences include a code to identify the respective ~~base station~~ broadcasting terminal.

34. (Previously Presented) The apparatus of Claim 30, wherein the respective broadcast information sequences include a power sequence that is related to the power used to transmit the respective broadcast message.

35. (Currently Amended) The apparatus of Claim 30, wherein the respective broadcast information sequences include a load sequence that is related to the current traffic load at the respective ~~base station~~ broadcasting terminal.

36. (Currently Amended) An apparatus comprising:

means for transmitting a first broadcast message in a broadcast channel at a first specific time within a first assigned slot of a predetermined frame from a first ~~base station~~ broadcasting terminal of a radio communications system, the first broadcast message including a first broadcast information sequence;

means for transmitting a second broadcast message in the broadcast channel at a second specific time within a second assigned slot of the predetermined frame from a second ~~base station~~ broadcasting terminal of the radio communications system, the second broadcast message including a second broadcast information sequence; and

means for receiving a message from a user terminal ~~at the first base station~~, the received message being timed relative to the first broadcast message to distinguish the received message as being directed to the first broadcasting terminal, ~~having a timing relationship with the predetermined frame; and~~

~~means for determining at the first base station whether the received message is directed to the first base station or not directed to the first base station based on the timing relationship.~~

37. (Currently Amended) The apparatus of Claim 36, further comprising means for transmitting further broadcast messages in the broadcast channel at further specific times within further assigned slots of a predetermined frame from further ~~base stations~~ broadcasting terminals of the radio communications system, the further broadcast messages including further broadcast information sequences .

38. (Original) The apparatus of Claim 36, means for receiving a common timing reference and means for determining the specific transmission times based on the common timing reference.

39. (Currently Amended) The apparatus of Claim 36, wherein the respective broadcast information sequences include a code to identify the ~~base station~~ broadcasting terminal.

40. (Currently Amended) The apparatus of Claim 36, wherein the code to identify the ~~base station~~ broadcasting terminal comprises a base station color code.

41. (Previously Presented) The apparatus of Claim 36, wherein the respective broadcast information sequences include a power sequence that is related to the power used to transmit the respective broadcast message.

42. (Currently Amended) The apparatus of Claim 36, wherein the respective broadcast information sequences include a load sequence that is related to the current traffic load at the respective ~~base station~~ broadcasting terminal.

43. (Currently Amended) A broadcast channel in a radio communications system, the channel comprising:

a repeating frame shared by a plurality of ~~base stations~~ broadcasting terminals, the frame having a plurality of slots, each ~~base station~~ broadcasting terminal being assigned to a slot;

a predetermined timing assigned to each slot, so that each slot of the frame is synchronized at all ~~base stations~~ broadcasting terminals;

a broadcast burst message for each ~~base station~~ broadcasting terminal, for transmission in the respective assigned slot, the burst message having a broadcast information sequence ~~that includes a power sequence that is related to the power used to transmit the broadcast message~~; and

an uplink request channel having a plurality of slots to allow a user terminal to request a traffic channel, each slot of the uplink request channel having a timing relationship with the slots of the repeating frame to distinguish uplink requests sent to different ones of several nearby broadcasting terminals ~~so that the timing relationship indicates the base station to which the traffic channel request is directed~~.

44. (Currently Amended) The channel of Claim 43, wherein the broadcast information sequence includes a code to identify the transmitting ~~base station~~ broadcasting terminal.

45. (Currently Amended) The channel of Claim 43, wherein the predetermined timing is based on a common timing reference received by each ~~base station~~ broadcasting terminal.

46. (Currently Amended) The channel of Claim 45, wherein the common timing reference is a satellite clock transmission received in a satellite receiver at each ~~base station~~ broadcasting terminal.

47. (Original) The channel of Claim 43, further comprising a frequency hopping sequence.

48. (Currently Amended) A method for accessing a wireless network, comprising:

receiving a plurality of timing sequences on a broadcast channel, each timing sequence being received from a different one of a plurality of ~~base stations~~ broadcasting terminals;

determining network timing using the received timing sequences;

selecting one from among the plurality of ~~base stations~~ broadcasting terminals using the received timing sequences;

transmitting a message to the selected ~~base station~~ broadcasting terminal, the message being timed relative to having a timing relationship with a selected one of the timing sequences to distinguish the message as being directed to the selected one of the

Attorney Docket No. 015685P052
Application No. 09/675,274

~~timing sequences wherein the timing relationship indicates the selected one from among the plurality of base stations to which the message is transmitted.~~

49. (Currently Amended) The method of Claim 48, wherein the timing sequences are received with at least one frequency and wherein the method further comprises using the received timing sequences to determine a base station broadcasting terminal selection message frequency based on the frequency of the received timing sequences.

50. (Original) The method of Claim 48, wherein the message is transmitted omnidirectionally.

51. (Currently Amended) The method of Claim 48, wherein the timing sequences are synchronized based on a common timing reference received by each ~~base station~~ base station broadcasting terminal.

52. (Currently Amended) The method of Claim 51, wherein the common timing reference is a satellite clock transmission received in a satellite receiver at each ~~base station~~ base station broadcasting terminal.

53. (Currently Amended) The method of Claim 48, further comprising receiving ~~base station~~ base station broadcasting terminal identifiers on the broadcast channel, the ~~base station~~ base station broadcasting terminal identifiers each being associated with a respective timing sequence and using the ~~base station~~ base station broadcasting terminal identifiers to distinguish broadcasts from different ~~base stations~~ base station broadcasting terminals on the broadcast channel.

54. (Currently Amended) The method of Claim 53, wherein transmitting a base-station broadcasting terminal selection message further comprises transmitting a base-station broadcasting terminal identifier.

55. (Currently Amended) The method of Claim 48, wherein transmitting a base-station broadcasting terminal selection message further comprises transmitting an identifier of the transmitter.

56. (Currently Amended) A machine-readable medium having stored thereon data representing sequences of instructions which, when executed by a machine, cause the machine to perform operations comprising:

receiving a plurality of timing sequences on a broadcast channel, each timing sequence being received from a different one of a plurality of base-stations broadcasting terminals;

determining network timing using the received timing sequences;

selecting one from among the plurality of base-stations broadcasting terminals using the received timing sequences;

transmitting a message to the selected base-station broadcasting terminal, the message being timed relative to having a timing relationship with a selected one of the timing sequences to distinguish the message as being directed to the selected one of the timing sequences wherein the timing relationship indicates the selected one from among the plurality of base stations to which the message is transmitted.

57. (Currently Amended) The medium of Claim 56, wherein the timing sequences are received with at least one frequency, the instructions further causing the machine to perform operations comprising using the received timing sequences to determine a ~~base station~~ broadcasting terminal selection message frequency based on the frequency of the received timing sequences.

58. (Currently Amended) The medium of Claim 56, the instructions causing the machine to perform further operations comprising synchronizing the timing sequences based on a common timing reference received by each ~~base station~~ broadcasting terminal.

59. (Currently Amended) The medium of Claim 56, the instructions causing the machine to perform further operations comprising receiving ~~base station~~ broadcasting terminal identifiers on the broadcast channel, the ~~base station~~ broadcasting terminal identifiers each being associated with a respective timing sequence and using the ~~base station~~ broadcasting terminal identifiers to distinguish broadcasts from different ~~base station~~ broadcasting terminal s on the broadcast channel.

60. (Currently Amended) The medium of Claim 56, wherein transmitting a ~~base station~~ broadcasting terminal selection message further comprises transmitting a ~~base station~~ broadcasting terminal identifier.

61. (Currently Amended) The medium of Claim 56, wherein the instructions for transmitting a ~~base station~~ broadcasting terminal selection message further comprise instructions causing the machine to perform operations comprising transmitting an identifier of the transmitter.